



Features:

- All 12 adapters in kit are direct. **No intermediate couplers.**
- Reduced signal loss in adapters due to absence of couplers.
- Kit includes the most frequently used N Type adapters including N / N, N / SMA, N / BNC, and N Terminations, both 50 and 75 ohm. See complete list in drawing or in table below.
- Rugged, lockable, pistol-grip case.
- All parts precision machined brass with tarnish resistant gold or nickel plating.
- Male center pins are gold plated brass.
- Female contacts are gold plated heat treated beryllium copper.
- Insulation material is high density PTFE.



**Order Example: 72932
(N Adapter Kit)**

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
 All specifications are to the latest revisions. Specifications are subject to change without notice.
 Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)
 For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com

| Item | Description | Pomona Part Number | NOM. IMPEDANCE | FREQ. RANGE | VSWR | OPERATING TEMP |
|------|-----------------------------|--------------------|----------------|---------------|-------------------|------------------|
| 1 | TYPE N female/male RA | 3843 | 50 Ohms | DC to 11GHz | 1.35 to 11GHz | - 65° to +165° C |
| 2 | TYPE N Terminator plug | 4240-75 | 75 Ohms | DC to 500 MHz | 1.35 at 500 MHz | - 65° to +165° C |
| 3 | TYPE N Terminator plug | 4240-50 | 50 OHMS | DC to 500 MHz | 1.35 at 500 MHz | - 65° to +165° C |
| 4 | TYPE N female/female | 3841 | 50 Ohms | DC to 11GHz | 1.35 to 11GHz | - 65° to +165° C |
| 5 | BNC male/ TYPE N female | 3535 | 50 Ohms | DC to 4 GHz | 1.35 to 4 GHz | - 65° to +165° C |
| 6 | BNC female, TYPE N male | 3288 | 50 Ohms | DC to 4 GHz | 1.35 to 4 GHz | - 65° to +165° C |
| 7 | SMA Termination male | 4286 | 50 Ohms | DC to 18GHz | 1.25 Max at 18GHz | - 65° to +165° C |
| 8 | TYPE N male/ TYPE N male | 3842 | 50 Ohms | DC to 11GHz | 1.35 to 11GHz | - 65° to +165° C |
| 9 | TYPE N female/female/female | 5089 | 50 Ohms | DC to 11GHz | 1.35 to 11GHz | - 65° to +165° C |
| 10 | SMA female/ TYPE N female | 4299 | 50 Ohms | DC to 11GHz | 1.35 to 11GHz | - 65° to +165° C |
| 11 | SMA male/TYPE N female | 4298 | 50 Ohms | DC to 11GHz | 1.35 to 11GHz | - 65° to +165° C |
| 12 | SMA female/TYPE N male | 4297 | 50 Ohms | DC to 11GHz | 1.35 to 11GHz | - 65° to +165° C |

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)

For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com